

IDS 12 / 16

**RUBBER FLOORING FOR
SCRAPED WALKING AREAS,
MILKING PARLORS AND
WAITING AREAS**



**CUSTOM DIMENSIONS
ON REQUEST**



COMFORT

Soft non-slip hammered upper side.
Reduces the risks of falling and the stress of the animal.

INSTALLATION

Jointless laying.
Few fixings.
Installation instructions provided.
No gluing.


HYGIENE

Compatible with many scrapers.
High pressure washing.
Resistant to most cleaning products.

RELIABILITY

High resistance to abrasion.
Lowered veterinary costs and improved heat detection.
Textile insertion.

RUBBER



Textile insertion



Custom length and width on request



6.2 / 6.5 x 60 mm steel nails

| Reference | Width | Length | Thickness | Weight | Units / palet | Units / container |
|-----------|--|------------|-----------|------------------------|---------------|-------------------|
| IDS12T | Standard: 1,00 - 1,20 - 1,50 - 1,60 - 1,80 - 2,00 m or custom dimensions up to 2,00 m | Up to 50 m | 12 mm | 13,9 kg/m ² | 1 roll | 15 to 18 rolls |
| IDS16T | Standard: 1,50 - 1,60 - 1,80 - 2,00 m or custom dimensions up to 2,00 m | Up to 50 m | 16 mm | 21,2 kg/m ² | 1 roll | 8 to 10 rolls |

